Overview of ROMEX® products

Product	Optimal areas of application	Joint width	Joint depth		Load	Water permeability	Container	Pag
ROMPOX® - JOINTING SAND NP	 Around the house and commercial areas, driveways Tightly laid paving stone and slabs Interlocking paving 	> 1 mm	> 30 mm		All load classes	Highly permeable	25 kg bag	9
ROMPOX® - D7000 JOINT STRENGTHENER	Around the house and commercial areasDrivewaysPermanent hardening of JOINTING SAND NP	> 1 mm	> 30 mm		Light traffic load up to 3 t	Joints remain water-permeable	1 liter bottle 20 liter canister	C
ROMPOX® - ECOFINE	 Around the house Surfaces around pools Tightly laid paving and slabs	> 3 mm	> 30 mm		Light traffic load up to 3.5 t	Highly permeable	12.5 kg bucket 25 kg bucket	1
ROMPOX® - EASY	 Around the house Terraces, garden paths Almost all coated and sensitive stones	> 5 mm	> 30 mm		Light traffic load up to 3.5 t	Highly permeable	15 kg bucket 25 kg bucket	
ROMPOX® - DRAIN	 Around the house Driveways, parking spaces Almost all coated and sensitive stones	> 3 mm	> 30 mm	₩.	Light traffic load up to 3.5 t	Highly permeable	25 kg bucket	
ROMPOX® - D1	Around the house and commercial areasDriveways, parking spacesFlagstones and crazy paving	> 3 mm	> 30 mm		Average traffic load up to 7.5 t	Highly permeable	27.5 kg bag 25 kg bucket	
ROMPOX® - D2000	Heavily used public areasRenovation of old paving	> 5 mm	> 30 mm		Medium to heavy traffic load up to 25 t	Permeable	27.5 kg bag	
ROMPOX® - TRAFFIC V2	Extremely busy public areasSquares, roads and traffic circles	> 8 mm	> 30 mm		Highest traffic load up to 40 t	Permeable	28 kg bag	
ROMPOX® - W1000	Heavily used public areas	> 8 mm	> 30 mm		Highest traffic load up to 40 t	Permeable	28 kg bag	
ROMPOX® - 301 CEM-PF	Surfaces in rail areasIn hydraulic engineeringCan be used for old and new plaster	> 3 mm	> 40 mm		Highest traffic load up to 40 t	Impermeable	25 kg bag	
ISATEC® - FLEX	Heavily used public areas Concrete blocks and slabs	> 5 mm	> 30 mm		Highest traffic load up to 40 t in combination with ISATEC® - STOP up to Bk3.2	Permeable	25 kg bucket	
ROMPOX® - D3000	Public areasRenovation of defective cement surfacesRenovation of old paving	> 3 mm	> 10 mm joint crack depth		Medium to heavy traffic load up to 25 t	Highly permeable	27.5 kg bag	
ROMPOX® - D4000	Renovation, repair in the public sector	Surface depth > 10 mm			Highest traffic load up to 40 t	Permeable	17.5 kg bucket	
ROMPOX® - D4000 HR	Renovation, repair in the public sector	Surface depth > 10 mm			Highest traffic load up to 40 t	Permeable	17.5 kg bucket	
ROMPOX® - 302 CEM-TB (TRASS BEDDING)	Around the house and public areas	> 3 cm layer thickness			Highest traffic load up to 40 t	Highly permeable	25 kg bag	
ROMPOX® - 303 CEM-TC (TRASS-BEDDING-COMPOUND)	Around the house and public areas	> 3 cm layer thickness			Highest traffic load up to 40 t	Highly permeable	25 kg bag	
ROMPOX® - 304 CEM-HS (ADHESION ELUTRIANT)	Around the house and public areas	> 3 mm layer thickness			Highest traffic load up to 40 t	Impermeable	25 kg bag	
ROMPOX® - 201 DEKO UV	Private driveways, parking spacesPublicly used footpathsAll grit and gravel, especially for light-colored rocks	Surface depth > 20 mm		₩.	Light traffic load up to 3 t	Highly permeable	1.25 kg double chamber bag, 30 kg container	
ROMPOX® - 202 DEKO EP (PROFI-DEKO)	Private driveways, parking spacesPublicly used footpathsFor dark grit and gravel	Surface depth > 20 mm		₽	Light traffic load up to 3 t	Highly permeable	3 kg bottle pack 30 kg container	

